

ECOFLOW

新世代環保電能站

X-STREAM
內置 X-STREAM 快充技術

X-BOOST
驅動技術

**1小時快速
回充技術**

原裝行貨 **3年**保用*



EcoFlow 香港總代理:



OTG OnTheGo Limited
創動樂有限公司

場景應用

戶外應用

- 車中泊
- 戶外展覽會
- 戶外流動充電



緊急應用

- 家中後備電源
- 工程
- 緊急救護站
- 搜救支援



專業應用

- 攝製工作
- 戶外工程
- 環境監測



EcoFlow 產品技術

X-Stream (專利技術)

EcoFlow 的X-Stream 閃電快充技術是市場上最快的充電方案之一，使用內置的智能逆變器，EcoFlow的電池最快可於1小時內充滿

X-Boost

EcoFlow 的X-Boost 升維驅動功能，令你的電池能推動比額定輸出更高功耗的電器，這個獨有的技術在重要關頭令你的電器也可維持限度運作 (建議實際使用前先作測試)

Smart BMS (電池管理系統)

系統為你的電池健康作全方位監察，確保使用安全及維持高效

EcoFlow APP

EcoFlow 手機程式支援大部份便攜電源產品，電量狀態、功能控制，全由你遙距一手掌握

EPS (Emergency Power Supply)

可將家中不可斷電的設備通過EcoFlow 電源與市電相連，如遇市電斷電的情況，EcoFlow可在30毫秒內自動切換到電池供電模式，保障重要設備持續工作不斷電 (建議實際使用前先作測試)

RIVER 2			
Model	EcoFlow RIVER 2	EcoFlow RIVER 2 Max	EcoFlow RIVER 2 Pro
Capacity	256Wh	512Wh	768Wh
Battery Type	Lithium-ion (LFP)	Lithium-ion (LFP)	Lithium-ion (LFP)
Life Cycles	3000 cycles to 80% capacity	3000 cycles to 80% capacity	3000 cycles to 80% capacity
AC Output	300W (surge 600W)	500W (surge 1000W)	800W (surge 1600W)
AC Output Sockets	1	2	3
Type-C PD Ports	1 (60W)	1 (100W)	1 (100W)
Total Ports	5	9	10
Wall Charging	360W max	660W max	940W max
Wall Charging Time	1 Hr	1 Hr	1.2 Hrs
Universal Solar Charging	Yes (XT60 socket)	Yes (XT60 socket)	Yes (XT60 socket)
Solar Panel Charging Time	3 - 4 Hours (110W x 1)	3 - 4 Hours (110W x 2)	4 - 8 Hours (110W x 2)
APP control	Supported	Supported	Supported
Dimensions	245×214×142mm	270×260×196mm	270×260×226mm
Weight	3.5kg	6kg	7.8kg
Warranty Year*	3	3	3
Price (HKD)	\$ 2,580	\$ 3,980	\$ 4,980

SOLAR PANELS			
Model	EcoFlow Solar Panel 110W	EcoFlow Bifacial Solar Panel 220W	EcoFlow Solar Panel 400W
Rated Power	110W	220W *Front Side 155W *Rear Side	400W
Efficiency	22.8%	22% - 23%	22.6%
Cell Type	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon
Connector Type	Solar connector	Solar connector	Solar connector
Dimensions (unfolded)	420×480×25mm	820×500×32mm	1058×620×25mm
Dimensions (folded)	420×1785×25mm	820×1835×25mm	1058×2365×25mm
IP Ratings	IP68	IP68	IP68
Net Weight	4kg	9.5kg	16kg
Warranty Year	1	1	1
Price (HKD)	\$ 1,980	\$ 4,680	\$ 8,280

DELTA 2						
Model	EcoFlow DELTA 2	EcoFlow DELTA 2 Smart Extra Battery	EcoFlow DELTA 2 MAX	EcoFlow DELTA 2 Max Smart Extra Battery	EcoFlow DELTA Pro	EcoFlow DELTA Pro Smart Extra Battery
Capacity	1024Wh	1024Wh	2048Wh	2048Wh	3600Wh	3600Wh
Battery Type	Lithium-ion (LFP)	Lithium-ion (LFP)	Lithium-ion (LFP)	Lithium-ion (LFP)	Lithium-ion (LFP)	Lithium-ion (LFP)
Life Cycles	3000 cycle to 80% capacity	3000 cycle to 80% capacity	3000 cycle to 80% capacity	3000 cycle to 80% capacity	3500 cycle to 80% capacity	3500 cycle to 80% capacity
AC Output	1800W (surge 2700W)	-	2400W (surge 4800W)	-	3600W (surge 7200W)	-
AC Output Sockets	4	-	4	-	4	-
Type-C PD Ports	2 (100W)	-	2 (100W)	-	2 (100W)	-
Total Ports	13	-	13	-	13	-
Wall Charging	1200W max	-	2300W max	-	2900W max	-
Wall Charging Time	1.4 Hrs	-	2 Hrs	-	1.9 Hrs	-
Universal Solar Charging	Yes (XT60 socket)	-	Yes (XT60 socket)	-	Yes (XT60 socket)	-
Solar Panel Charging Time*	3 - 4 Hours (110W x 4)	-	3 - 4 Hours (400W x 2)	-	3 Hours (400W x 3)	-
APP control	Supported	-	Supported	-	Supported	-
Dimensions	400×211×281mm	400×211×281mm	497×242×305mm	464×235×283mm	635×284×420mm	635×285×416mm
Weight	12kg	9.5kg	22.3kg	19kg	45kg	38kg
Warranty Year*	3	3	3	3	3	3
Price (HKD)	\$ 7,980	\$ 5,580	\$ 11,980	\$ 7,680	\$ 29,980	\$ 23,980

* DELTA系列同時支援使用多於2塊太陽能板充電，請參閱產品說明書

(V2023.08)

